

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
16 June 2005 (16.06.2005)

PCT

(10) International Publication Number  
**WO 2005/054050 A3**

(51) International Patent Classification<sup>7</sup>: **B63H 25/00**

21403 (US). JEFFERSON, James, R. [US/US]; 13 Southgate Avenue, Annapolis, MD 21401 (US).

(21) International Application Number:  
PCT/US2004/039936

(74) Agent: KLIMA, Timothy, J.; 500 Ninth Street SE, Washington, DC 20003 (US).

(22) International Filing Date: 1 December 2004 (01.12.2004)

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
60/525,888 1 December 2003 (01.12.2003) US

(71) Applicant (for all designated States except US): **ROLLS-ROYCE NAVAL MARINE, INC.** [US/US]; 110 Norfolk Street, Walpole, MA 02081 (US).


(72) Inventors; and

(75) Inventors/Applicants (for US only): **BARRETT, Andrew, F.** [US/US]; 1213 Marda Lane, Annapolis, MD

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),

[Continued on next page]

(54) Title: CONTROL OF A WATERJET PROPELLED VESSEL



(57) Abstract: A method for controlling a watercraft includes acquiring a desired heading of the watercraft, acquiring an actual heading of the watercraft at time  $T_0$ , calculating a heading error by comparing the desired heading with the actual heading and determining a rate of change of the heading error. A P gain, I gain and D gain for use in maintaining the heading of the watercraft is determined and used to calculate factors related to heading error, cumulative heading error and rate of change of heading error. These factors are summed to form a control value for deflecting a nozzle of the watercraft to maintain a heading of the watercraft. Further embodiments include methods for calculating and correcting a heading of the watercraft, as well as methods for controlling roll out and sideways motion of the watercraft.



European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

**Published:**

— with international search report

**(88) Date of publication of the international search report:**

10 November 2005

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*